

PACKAGED ROOF TOP COOLING UNIT SCHEDULE (AIR COOLED)

UNIT NO.	AREA SERVED	LOCATION	TONS	BLOWER SECTION						COOLING CAPACITY (MBH)					EVAPORATOR				COMPRESSORS			HEATING				ELECTRICAL DATA				UNIT WEIGHT (LBS)	MANUFACTURER MODEL NO.	REMARKS		
				TOTAL SUPPLY AIR CFM	TOTAL R.A. CFM	OA CFM	EXT. S.F.	BRAKE HP	SP. RPM	TOTAL	SENS.	E.A.T. (°F DB)	FACE AREA	E.A.T. (°F) OB	L.A.T. (°F) WB	E.A.T. (°F) OB	L.A.T. (°F) WB	NUMBER	REFRIGERANT	AIR FEE	SEER	TYPE	E.A.T. (°F)	L.A.T. (°F)	INPUT (MBH)	OUTPUT (MBH)	VOLTS	PHASE/Hz	FLA				MCA	MICOD
RTU-1	GYM		5	2000	2000	100	0.5	1.5	1.5	1050	57.5	26.8	78.7	7.52	78.7	71.8	66.4	62.8	1	R410A	11.2	14	N.G.	68.9	124.3	120	97.2	208-230	3/Ø	34	45	583	RHEIM R66C2R050AC112BACCA1	
RTU-2	GYM		5	2000	2000	100	0.5	1.5	1.5	1050	57.5	26.8	78.7	7.52	78.7	71.8	66.4	62.8	1	R410A	11.2	14	N.G.	68.9	124.3	120	97.2	208-230	3/Ø	34	45	583	RHEIM R66C2R050AC112BACCA1	
RTU-3	GYM		5	2000	2000	100	0.5	1.5	1.5	1050	57.5	26.8	78.7	7.52	78.7	71.8	66.4	62.8	1	R410A	11.2	14	N.G.	68.9	124.3	120	97.2	208-230	3/Ø	34	45	583	RHEIM R66C2R050AC112BACCA1	
RTU-4	GYM		5	2000	2000	100	0.5	1.5	1.5	1050	57.5	26.8	78.7	7.52	78.7	71.8	66.4	62.8	1	R410A	11.2	14	N.G.	68.9	124.3	120	97.2	208-230	3/Ø	34	45	583	RHEIM R66C2R050AC112BACCA1	

- PROVIDE THE FOLLOWING ACCESSORY FOR UNITS:
1. PROVIDE 24" TALL KNOCKED DOWN ROOF CURB
 2. PROVIDE 2" THICK POLYURETHANE THERMOBARRIER FILTERS
 3. PROVIDE UNITS WITH SINGLE ENTHALPY FRESH AIR ECONOMIZER W/CONTROLS, HINGED ACCESS PANELS
 4. PROVIDE CONDENSATE TRAP PER MANUFACTURER'S RECOMMENDATIONS AND CONDENSATE OVERFLOW SWITCH
 5. PROVIDE 7-DAY PROGRAMMABLE THERMOSTAT WITH HANDL PROOF PLASTIC COVER
 6. PROVIDE CONCENTRIC ADAPTER 5/8 TON DROP
 7. PROVIDE CONCENTRIC DIFFUSER 5/8 TON DROP
 8. PROVIDE UNITS WITH 2-STAGE GAS HEATING WITH STAINLESS STEEL HEAT EXCHANGERS
 9. PROVIDE NATURAL GAS TO PROPANE CONVERSION KIT